

./kamaki - Feature # 4810

<b>Status:</b>	Resolved	<b>Priority:</b>	Medium
<b>Author:</b>	Stavros Sachtouris	<b>Category:</b>	kamaki
<b>Created:</b>	12/23/2013	<b>Assignee:</b>	Stavros Sachtouris
<b>Updated:</b>	02/05/2014	<b>Due date:</b>	01/18/2014
<b>Subject:</b>	Allow pithos commands to recognise users by username		
<b>Description</b>			
<p>The <del>A/</del> <i>-account</i> argument, if failed to match a user UUID, should try to match a user name instead and resolve the UUID from that. This might cost an extra http request per call, but it will improve the intuitiveness of all pithos-related commands that can refer to shared objects</p>			

Associated revisions

Revision 023d5ada - 02/05/2014 03:16 pm - Stavros Sachtouris

Recognise usernames in --account args (or similar)

Refs: #4810

Arguments --account and --to-account can now accept usernames along with uuids  
Kamaki attempts to recognise the argument as a uuid. In case of failure, it attempts to recognise it as a username. If it fails again, it produces an error.

Also, restore kamaki file publish/unpublish

History

#1 - 02/05/2014 03:25 pm - Stavros Sachtouris

- Status changed from Assigned to Resolved
- % Done changed from 0 to 100