./kamaki - Feature # 5051

Status:	New	**Priority:**	Medium
Author:	Stavros Sachtouris	**Category:**	
Created:	02/10/2014	**Assignee:**	
Updated:	02/10/2014	**Due date:**	02/14/2014
Subject:	Semanticly clean up responses		

Description

This feature affects almost all commands that perform HTTP requests and show their results.
Prune the tree of results so that it is as close as possible to the semantics of the command.
For example, up to the current version:

```
$ kamaki quota list
system:
  cyclades.disk:
    usage: 0B
    limit: 100GiB
    pending: 0B
  cyclades.vm:
    usage: 0
    limit: 2
    pending: 1
  ...
```

The "system" key is part of the response, but does not add anything semanticaly. If anything, it creates confusion. The following response is more apropriate:

```
cyclades.disk:
  usage: 0B
  limit: 100GiB
  pending: 0B
cyclades.vm:
  usage: 0
  limit: 2
  pending: 1
...
```

Related issues:

related to ./kamaki - Feature # 4811: Add match and filter arguments in listi...	**New**	**12/23/2013**	**02/07/2014**

Associated revisions

Revision c75be81a - 02/11/2014 06:08 pm - Stavros Sachtouris

Pretty server info, better errors in set firewall

Refs: #5051

Revision 4c33b869 - 02/12/2014 11:43 am - Stavros Sachtouris

Remove obsolete arguyments from server_info

Refs: #5051

History